

### SVCM0005 & SVCM0004

Color Digital Box Camera

#### Feature

- 1/4" Sharp or 1/3" Sony color CCD
- Horizontal resolution of 420TV Lines
- Minimum illumination of 0.8 Lux
- Electronic shutter of 1/50-1/10,0000 seconds
- S/N ratio of more than 48dB
- DC/VIDEO lens drive: fit to any DC/VIDEO drive lens
- With audio
- Easy to plug and fix



Item	SVCM0005	SVCM0004
System	PAL / NTSC	
Image Sensor	1/4 " SHARP COLOR CCD	1/3" SONY COLOR CCD
Picture Elements	PAL: 512(H) x 582 (V) / NTSC: 512(H) x 492 (V)	
Video output	1.0Vp-p, 75Ω Composite, BNCx1	
Horizontal resolution	420TVL	
S/N Ratio	? 48dB	
Minimum illumination	0.8 LUX/F1.2	
Sync system	2:1 interlace internal Sync.	
Shutter	1/50-1/10,0000S	
Gamma Ratio	0.45	
Auto White Balance	On/Off	
Auto Gain Control	On/Off	
Lens Mount	6mm/F1.2	
Operating Temperature	Outdoor: -10? to 50?	
Humidity	0 to 90% RH (non-condensing)	
Power	DC12V,1000mA	
Weight	Approx.303g	

### SVCM0001 & SVCM0002

Color Dome Camera

#### Feature

- 1/4" Sony or 1/3" Sony color CCD
- Horizontal resolution of 420TV Lines
- Inbuilt 3.6/6/8/12mm fixed Lens
- Electronic shutter of 1/50-1/10,0000 seconds
- S/N ratio of more than 48dB
- Easy to plug and use



Item	SVCM0001	SVCM0002
System	PAL / NTSC	
Image Sensor	1/4 " SONY COLOR CCD	1/3" SONY COLOR CCD
Picture Elements	PAL: 512(H) x 582 (V) / NTSC: 512(H) x 492 (V)	
Video output	1.0Vp-p, 75Ω Composite, BNCx1	
Horizontal resolution	420TVL	
S/N Ratio	?48dB	
Minimum illumination	1.0 LUX/F1.2 OLUX (IR ON)	0.8 LUX/F1.2 OLUX (IR ON)
Sync system	2:1 interlace internal Sync.	
Shutter	1/50-1/10,0000S	
Day/Night mode	Auto	
Gamma Ratio	0.45	
Lens Mount	2.8/3.6/6/8/12 mm lens optional	
Operating Temperature	Outdoor: -10? to 50?	
Humidity	0 to 90% RH (non-condensing)	
Power	DC12V,1000mA	
Dimension	117(φ) × 100(H)mm	
Weight	Approx.210g	

### SVCM0008 & SVCM0007

Infrared Waterproof Camera

#### Feature

- 1/4" Sharp or 1/3" Sony color CCD
- 12PCS ? 5 IR LED, LED effective time up to 20,000hours
- Infrared irradiate distance 10~20m at night
- Day & Night Function mode selection (Auto)
- Infrared light turn on automatic (low illumination)
- Horizontal resolution of 420TV Lines
- Inbuilt 3.6/6/8/12 mm fixed Lens
- 24 hours surveillance
- Minimum illumination of 0 Lux (LED on)
- Electronic shutter of 1/50-1/10,0000 seconds
- S/N ratio of more than 48dB
- Auto back light compensation, auto electron shutter, auto gain control
- DC/VIDEO lens drive: fit to any DC/VIDEO drive lens



Item	SVCM0008	SVCM0007
System	PAL / NTSC	
Image Sensor	1/4 " SHARP COLOR CCD	1/3" SONY COLOR CCD
Picture Elements	PAL: 512(H) x 582 (V) / NTSC: 512(H) x 492 (V)	
Video output	1.0Vp-p, 75Ω Composite, BNCx1	
Horizontal resolution	420TVL	
S/N Ratio	?48dB	
Minimum illumination	1.0 LUX OLUX (IR ON)	0.5 LUX, OLUX (IR ON)
Sync system	2:1 interlace internal Sync.	
Shutter	1/50-1/10,0000S	
Day/Night mode	Auto	
Gamma Ratio	0.45	
Infrared distance	10~20m	
Lens Mount	6mm/F1.2	
Operating Temperature	Outdoor: -10? to 50?	
Humidity	0 to 90% RH (non-condensing)	
Power	DC12V,1000mA	
Weight	Approx.226g	